

Kinro

The Clear Choice

Series 7500 Aluminum Rolling Glass Door



Features and Benefits

- *Standard Frame* for use with all wall/siding types. *Lap Frame* with integral siding pocket that eliminates the need for additional siding trim pieces.
- Available in a variety of tempered glazing options in single or insulated glass.
- 5/8 inch sealed insulating glass (tempered) with optional Low-E provides optimum thermal performance.
- Heavy duty fin seal weather-strip to reduce air, water, dust and noise infiltration.
- Fully adjustable factory lubricated steel tandem rollers mounted with ball bearing ensures trouble free operation.
- Anti-rattle snigger bumper feature in lock jamb keeps the moving panel snug and tight.
- Color coordinated attractive clam type keyed lock mounted on hollow lock jamb for strength and sturdiness that provides added security.
- Full length lip on lock jamb acts as lock strike, not requiring adjustments after the door is properly installed.
- Slide direction easily reversed from XO to OX or from OX to XO.

Technical Specifications

Call Width	Net Frame Size	Recommended Rough Opening
5'-0"	58 15/16"	59 1/4"
5'-6"	64 15/16"	65 1/4"
6'-0"	70 15/16"	71 1/4"
Call Height		
6'-0"	72 1/2"	72 3/4"
6'-4"	76 1/2"	76 3/4"
6'-8"	80 1/2"	80 3/4"

Minimum size that meets HUD 3280.105 egress requirement would be 5'-6" x 6'-4"

Certification

Meets or exceeds the performance requirement of AAMA 1701.2 Standard, Grade Wind Zone III, AAMA/NWDA 101/I.S.2 Standard, Grade SGD-R15.



Kinro Inc reserves the right to change sizes or details without notice. The customer assumes all risk for alterations made to Kinro products.

Kinro

The Clear Choice

Series 7500 Aluminum Rolling Glass Door



Features and Benefits

- *Standard Frame* for use with all wall/siding types. *Lap Frame* with integral siding pocket that eliminates the need for additional siding trim pieces.
- Available in a variety of tempered glazing options in single or insulated glass.
- 5/8 inch sealed insulating glass (tempered) with optional Low-E provides optimum thermal performance.
- Heavy duty fin seal weather-strip to reduce air, water, dust and noise infiltration.
- Fully adjustable factory lubricated steel tandem rollers mounted with ball bearing ensures trouble free operation.
- Anti-rattle snigger bumper feature in lock jamb keeps the moving panel snug and tight.
- Color coordinated attractive clam type keyed lock mounted on hollow lock jamb for strength and sturdiness that provides added security.
- Full length lip on lock jamb acts as lock strike, not requiring adjustments after the door is properly installed.
- Slide direction easily reversed from XO to OX or from OX to XO.

Technical Specifications

Call Width	Net Frame Size	Recommended Rough Opening
5'-0"	58 15/16"	59 1/4"
5'-6"	64 15/16"	65 1/4"
6'-0"	70 15/16"	71 1/4"
Call Height		
6'-0"	72 1/2"	72 3/4"
6'-4"	76 1/2"	76 3/4"
6'-8"	80 1/2"	80 3/4"

Minimum size that meets HUD 3280.105 egress requirement would be 5'-6" x 6'-4"

Certification

Meets or exceeds the performance requirement of AAMA 1701.2 Standard, Grade Wind Zone III, AAMA/NWDA 101/I.S.2 Standard, Grade SGD-R15.



Kinro Inc reserves the right to change sizes or details without notice. The customer assumes all risk for alterations made to Kinro products.